

WHITE-RODGERS CONTROLS

www.white-rodgers.com

INDEX

| | | | |
|--|-------------|---|-------------|
| AIR CLEANERS | | CONTROLS (<i>cont'd</i>) | |
| ELECTRONIC..... | 7-20 | SNAP DISC..... | 7-7 – 7-8 |
| ELECTROSTATIC | 7-20 | SNAP DISC AND FAN LIMIT | 7-8 – 7-9 |
| ELECTROSTATIC — A+2000 | 7-20 | SNAP DISC AND FAN LIMIT — ADJUSTABLE..... | 7-8 |
| MEDIA | 7-20 | WARM AIR — FAN AND LIMIT..... | 7-11 |
| AIR SWITCH — DUAL PURPOSE..... | 7-15 | ELECTRIC HEAT PRODUCTS..... | 7-18 – 7-19 |
| CONTACTORS..... | 7-15 | FAN RELAYS..... | 7-18 |
| CONTROLS | | GAS VALVES..... | 7-16 – 7-17 |
| BOARD MOUNT LIMIT | 7-11 | HUMIDIFIERS AND PARTS | 7-21 |
| BURNOUT CLEAN-UP FILTER DRIER..... | 7-11 | HUMIDISTAT | 7-19 |
| FURNACE CONTROL KITS..... | 7-12 | SERVICE PARTS | 7-7 |
| FURNACE — HOT SURFACE IGNITORS — | | THERMOSTATS | |
| SILICONE CARBIDE..... | 7-13 – 7-14 | GUARDS..... | 7-6 – 7-7 |
| HYDRONIC | 7-15 | LINE VOLTAGE | 7-2 |
| IGNITION COMPONENTS | 7-12 | REMOTE SENSORS | 7-6 |
| MISCELLANEOUS | 7-12 | SINGLE STAGE — NON-PROGRAMMABLE..... | 7-3 – 7-4 |
| OIL AND GAS BURNER..... | 7-14 | SINGLE STAGE — PROGRAMMABLE | 7-2 – 7-3 |
| OIL AND GAS BURNER — MILLIVOLT POWER | | SUB BASE | 7-7 |
| GENERATORS..... | 7-15 | UNIVERSAL NON-PROGRAMMABLE..... | 7-6 |
| OIL AND GAS BURNER — UNIVERSAL | | UNIVERSAL PROGRAMMABLE | 7-4 – 7-6 |
| THERMOCOUPLES..... | 7-14 | WALL PLATES | 7-7 |
| REFRIGERATION — DRIERS — | | WIFI..... | 7-2 |
| BI-DIRECTIONAL HEAT PUMP..... | 7-11 | TRANSFORMERS | 7-18 |
| REFRIGERATION — DRIERS — SUCTION LINE..... | 7-11 | UV LIGHTS AND ACCESSORIES | 7-19 |
| REFRIGERATION — LIQUID LINE FILTER | | UV ZONING | 7-7 |
| DRIERS..... | 7-10 | | |
| REFRIGERATION — MOISTURE INDICATORS | 7-11 | | |
| REFRIGERATION — TEMPERATURE..... | 7-10 | | |

Expert Service. Quality Products. Since 1960.

WHITE-RODGERS CONTROLS

www.white-roddgers.com

THERMOSTATS

WIFI

| ITEM # | MODEL | DESCRIPTION |
|--------|-------------|--|
| 751495 | 1F86U-42WFC | Emerson WiFi Thermostat, No 24V Common Wire required. Universal (1H/1C), Multi-stage (2H/2C), Heat Pump (3H/3C) Remote home temperature control and monitoring. Temperature and humidity alerts, programmable or non-programmable, Displays current weather conditions. W/E, W2, Y1, Y2, RC, RH, C, L, G, O/B. |



LINE VOLTAGE

| ITEM # | MODEL | DESCRIPTION |
|--------|-----------|--|
| 751412 | 1A10-651 | SPDT Thermostat, 36°F to 90°F Range, 1.5°F Differential, Setpoint Locking Option, Range Limiting Option, 8 AMP at 120VAC, 4 AMP at 240/277VAC, may be used with S29-21 or S29-22 Subbases. |
| 751422 | 1A66W-633 | Classic White, DPST Thermostat, Open on Rise, 40°F to 85°F, No Thermometer, with "Off" Position. |
| 751520 | 1G65-633 | Range: 40°F to 80°F (4°C to 26°C), Differential: 1.0°F, Switch Action: Open on rise, Resistive (Non-Inductive): 22.0A, 120VAC (2500W), 22.0A, 240VAC (5000W), 18.0A, 277VAC (5000W). |
| 751515 | 201-8 | SPST, Close on Rise Temperature Control, Coiled Bulb, 20°F to 90°F Range, Adjustable Differential 3°F to 20°F. |



1A10-651



1A66W-633



1G65-633



1E78-151



1F78-151



1F80-0261



1F97-1277

SINGLE STAGE — PROGRAMMABLE

| ITEM # | MODEL | DESCRIPTION |
|--------|-----------|---|
| 751461 | 1E78-151 | 70 Series Economy (1H/1C) 5+2 Day Programmable Digital Thermostat, 24 Volts or Millivolt, System Switch-Heat, Off, Cool, Fan Switch – Auto, On, Profile – Vertical, Battery Powered, Range 45-90°F, Terminals – RC, RH, W, Y, G. |
| 751487 | 1F78-151 | 70 Series Economy (1H/1C) 5+2 Day Programmable Digital Thermostat, Backlit Display, 24 Volts or Millivolt, System Switch – Heat, Off, Cool, Fan Switch – Auto, On, Profile – Horizontal, Battery Powered, Range 45-90°F, Terminals – RC, RH, W, Y, G, O, B. Accessories: Wall Plate F61-2550, Wall Plate with Junction Box Adapter F61-2510. |
| 751511 | 1F80-0261 | Blue 2" Display, (1H/1C) 5+1+1 Day Programmable Digital Thermostat, Backlit Display, 24 Volts or Millivolt, System Switch – Heat, Off, Cool, Fan Switch – Auto, On, Profile – Horizontal, Dual Power (System and/or Battery), Replaces 1F80-361, Range 45-90°F, Terminals – R, C, W, Y, G, O/B. Accessories: Wall Plate with Junction Box Adapter F61-2500. |
| 751521 | 1F97-1277 | 90 Series Blue Touchscreen Premium Universal (1H/1C) Program Choices: 7 Day, 5+1+1 Day or Non-Programmable Digital Thermostat, Backlit Display, 24 Volt, Digital Remote Sense Option, Backlit Display, 24 Volts or Millivolt, Auto Changeover, System Switch – Heat, Off, Cool, Auto, Fan Switch – Auto, On, Program Fan, Energy Management Recovery, Keypad Lockout, Profile – Horizontal, Dual Power with Optional "C" Connection and/or Batteries, Range 45-99°F, Terminals – RC, RH, C, W, Y, G, Mv, 6, O, B. |

(cont'd on next page)

WHITE-RODGERS CONTROLS

www.white-roddgers.com

THERMOSTATS (cont'd)

SINGLE STAGE — PROGRAMMABLE (cont'd)

| ITEM # | MODEL | DESCRIPTION |
|--------|-----------|--|
| 751540 | 1F80-0471 | 80 Series Blue (1H/1C) 5 +1 +1 Day Programmable Digital Thermostat, Lighted Display, 24 Volt or Millivolt, System Switch – Heat, Off, Cool, Auto, Fan Switch – Auto, On, Profile – Horizontal, Dual Power with Optional "C" Connection and/or Batteries, Range 45-90°F, Terminals – RC, RH, C, W, Y, G, O/B, Wall Plate F61-2634 (Included). |



1F80-0471

SINGLE STAGE — NON-PROGRAMMABLE

| ITEM # | MODEL | DESCRIPTION |
|--------|-----------|--|
| 751423 | 1C20-101 | (1H/0C) Setpoint Thermostat, 24 Volts, Snap-Action, Lowest Setting has "Off" Position, System Switch – (Heat Only), Fan Switch – None, Profile – Vertical Rounded, Range 50-90°F, Terminals – RH, W (MERCURY FREE) |
| 751425 | 1C26-101 | Single Stage (1H/1C) Setpoint Thermostat, 24 Volts, Snap-Action, System Switch – Heat, Off, Cool, Fan Switch – Auto, Continuous, Profile – Vertical Rounded, Range 50-90°F, Terminals – RH, RC, G, W, Y, O, B (MERCURY FREE) |
| 751447 | 1E30N-311 | (1H/0C) Setpoint Thermostat, Beige, 24 Volts, Sealed Mercury Cell, System Switch – (Heat Only), Fan Switch – None, Profile – Vertical, Range 50-90°F, Terminals – 4, 5 |
| 751454 | 1E50N-303 | (1H) Vertical Setpoint Thermostat, 24 Volts, Snap Action Contact, System Switch – Heat, Off, Fan Switch – None, includes Temperature Locking Kit, Terminals – RH, W, G. (MERCURY FREE) |
| 751457 | 1E56N-361 | Universal (1H/1C, or 1H, or 1C) Vertical Setpoint Thermostat, 24 Volts, Snap Action Contact, System Switch – Heat, Off, Cool, Fan. Switch-Auto, On, can be used on 3 wire zone valve and 750 mV applications, includes Heat/Cool Only Terminal Wall Plate, Terminals – RC, RH, W, Y, G, O, B, A. (MERCURY FREE) |
| 751456 | 1E65-144 | Electronic Line Voltage, SPST Thermostat, Open on Rise, 40° to 90°F, Silent Triac Operation, Large Room Temperature/Set Point Display, Lighted Display, Power Consumption Percentage Indicator (10-100%), Proportional Control Option, Permanent Setpoint Memory, Standby Mode. For use on Electric Baseboard, Radiant Floor, Radiant Ceiling, Convectors, and Fan Forced Heaters. |
| 751459 | 1E78-140 | 70 Series Economy (1H/0C) Digital Thermostat, 24 Volts or Millivolt, System Switch – Heat, Off, Fan Switch – Auto, On, Profile – Vertical, Battery Powered, Range 45-90°F, Terminals – RH, W, G. |
| 751460 | 1E78-144 | 70 Series Economy (1H/1C) Digital Thermostat, 24 Volts or Millivolt, System Switch – Heat, Off, Cool, Fan Switch – Auto, On, Profile – Vertical, Battery Powered, Range 45-90°F, Terminals – RC, RH, W, Y, G, O, B. |



1C20-101



1E50N-303



1E65-144



1E78-140



1E78-144

(cont'd on next page)

WHITE-RODGERS CONTROLS

www.white-rodgers.com

THERMOSTATS (cont'd)

SINGLE STAGE — NON-PROGRAMMABLE (cont'd)

| ITEM # | MODEL | DESCRIPTION |
|--------|-------------|--|
| 751477 | 1F56N-361 | (1H/1C, or 1H or 1C) Vertical Setpoint Thermostat, 24 Volts, Snap Action Contact, System Switch – Heat, Off, Fan Switch – None, Profile – Horizontal, includes Temperature Locking Kit, Terminals – RH, W, G. (MERCURY FREE) |
| 751486 | 1F78-144 | Series Economy (1H/1C) Digital Thermostat, Backlit Display, 24 Volts or Millivolt, System Switch – Heat, Off, Cool, Fan Switch – Auto, On, Profile – Horizontal, Battery Powered, Range 45-90°F, Terminals – RC, RH, W, Y, G, O, B. Accessories: Wall Plate F61-2550, Wall Plate with Junction Box Adapter F61-2510. |
| 751499 | 1F86-0244 | Blue 2" Display, (1H/1C) Digital Thermostat, Backlit Display, 24 Volts, System Switch – Heat, Off, Cool, Fan Switch – Auto, On, Profile – Horizontal, Battery Powered, Replaces 1F86-344, Range 45-90°F, Terminals – R, C, W, Y, G, O/B. Accessories: Wall Plate with Junction Box Adapter F61-2500. |
| 751552 | 1F86EZ-0251 | Blue 2" Display, Single Stage, Heat Pump (1H/1C) Non-Programmable Digital Thermostat, Home-Sleep-Away buttons. Backlit Display, 24 Volts, System Switch – Heat, Off, Cool, Fan Switch – Auto, On, Profile – Horizontal, Battery or Hardwired Powered, Range 45-90°F, Terminals – R, C, W, Y, G, O/B. Accessories: Wall Plate with Junction Box Adapter F61-2500. |
| 751542 | 1F86-0471 | 80 Series Blue (1H/1C) Digital Thermostat, Lighted Display, 24 Volt or Millivolt, System Switch – Heat, Off, Cool, Auto, Fan Switch – Auto, On, Profile – Horizontal, Dual Power with Optional "C" Connection and/or Batteries, Range 45-90°F, Terminals – RC, RH, C, W, Y, G, O/B, Accessories: Wall Plate F61-2634 (Included). |
| 751503 | 1F89-0211 | Blue 2" Display, Heat Pump (2H/1C) Non-Programmable Digital Thermostat, Backlit Display, 24 Volts, System Switch – Heat, Off, Cool, Emer. Auto, Fan Switch – Auto, On, Profile – Horizontal, Dual Power (System and/or Battery), Range 45-90°F, Terminals – R, C, G, Y, W2, O/B, L. Accessories: Wallplate with Junction Box Adapter F61-2500 |



1F78-144



1F86-0244



1F86EZ-0251



1F86-0471



1F89-0211

UNIVERSAL PROGRAMMABLE

| ITEM # | MODEL | DESCRIPTION |
|--------|-----------|--|
| 751500 | 1F82-0261 | Blue 2" Display, Heat Pump (2H/1C) 5+1+1 Programmable Digital Thermostat, Backlit Display, 24 Volts, System Switch – Heat, Off, Cool, Emer. Auto-Auto, On, Energy Management Recovery, Profile – Horizontal, Dual Power (System and/or Battery), Range 45-90°F, Terminals – R, C, G, Y, W2, O/B, L. Accessories: Wall Plate with Junction Box Adapter F61-2500. |
| 751548 | 1F85-0422 | 80 Series Universal Single Stage, Multi-Stage (2H/2C) or Heat Pump (2H/1C). Program Choices: 5+1+1 Day, 5+2 Day, or Non-Programmable Digital Thermostat, Backlit Display, 24 Volts or Millivolt, System Switch – Heat, Off, Cool, Auto, Emer., Fan Switch – Auto, On, Profile – Horizontal, Dual Power (R-C) and/or Batteries, Range 45-90°F. Terminals – RC, RH, C, G, W/E, W2, Y, Y2, O/B, 6, L. Includes F61-2634 Wall Plate. |



1F82-0261



1F85-0422

(cont'd on next page)

WHITE-RODGERS CONTROLS

www.white-roddgers.com

THERMOSTATS (cont'd)

UNIVERSAL PROGRAMMABLE (cont'd)

| ITEM # | MODEL | DESCRIPTION |
|--------|-------------|--|
| 751550 | 1F85-0477 | 80 Series Blue Universal Single Stage, Multi-Stage (2H/2C) or Heat Pump (3H/2C). Program Choices: 5+1+1 Day, 5+2 Day, or 7-day Programmable Digital Thermostat, Backlit Display, 24 Volts or Millivolt, System Switch – Heat, Off, Cool, Auto, Emer., Fan Switch – Auto, On, Profile – Horizontal, Dual Power (R-C) and/or Batteries, Range 45-90°F. Terminals – R, C, G, W/E, W2, Y, Y2, O/B/6, L. Includes F61-2634 Wall Plate. |
| 751506 | 1F95-1277 | 90 Series Blue Touchscreen Premium Universal Single Stage, Multi-Stage (2H/2C) or Heat Pump (3H/2C). Program Choices: 7 Day, 5+1+1 Day or Non-Programmable Digital Thermostat, Backlit Display, 24 Volt, Energy Management Recovery, Remote Sense Option, System, Switch-Heat, Off, Cool, Auto, Emer. Fan Switch – Auto, On, Program Fan, Profile – Horizontal, Dual Power with Optional "C" Connection and/or Batteries, Range 45-99°F, Terminals – RC, RH, C, G, W/E, W2, Y, Y2, L, O, B, 6. |
| 751532 | 1F95-0680 | Blue Commercial Multi-Stage (2H/2C) or Heat Pump (4H/2C) 7-Day programmable Digital Thermostat, Backlit Display, 24 Volts, 2 Programs, Economizer Control, Automatic Changeover, System Switch – Heat, Off, Cool, Emergency, Auto, Fan Switch – Auto, On, Programmable Fan, Energy Management Recovery, Remote Sense Option, Keypad Lockout, Profile – Horizontal, Tri-Power (Hardwire, Battery, Battery W/Power Stealing Assist), Range 45-99°F, Terminals – RC, RH, C, G, Y, Y2, W/E, W2, A1, 6, O/B, L, +, S, -. |
| 751536 | 1F95EZ-0671 | Blue Easy Reader Universal Compatible Single Stage (1H/1C), Multi-Stage (2H/2C) or Heat Pump up to (4H/2C). Program Choices: Non-Programmable or 7-Day program. Backlit Display, 24 Volts or Millivolt, System Switch – Heat, Off, Cool, Aux Heat, Fan Switch – Auto, On, Profile – Horizontal, Tri-Power (R-C) and/or Batteries w/optional power stealing assist, Range 45-90°F. Terminals – RC, RH, C, G, W/E, W2, Y, Y2, O/B, 6, L. |
| 751530 | 1F95-1291 | Blue Touchscreen Multi-Stage or Heat-Pump Thermostat (4H/2C) with Two Mode Dehumidification, Dual Fuel Option 7-Day Programmable, Backlit Display, 24 Volts, Automatic Changeover, System Switch – Heat, Off, Cool, Emergency, Auto, Fan Switch – Auto, On, Programmable Fan, Energy Management Recovery, Remote Sense Option, Keypad Lockout, Profile – Horizontal, Tripower (Hardwire, Power Stealing, Battery), Range 45-99°F, Terminals – RC, RH, C, G, Y1, Y2, W/E, W2, W2, O/B, L, +, S, -, DHM, HM. |
| 751538 | 1F98EZ-1441 | Blue Easy Install 12" Touchscreen 4 Wire Communicating System with F145-1328 Outdoor Sensor included. Universal Single Stage, Multi-Stage or Heat-Pump up to (4H/2C), with Humidification and/or Dehum, Dual Fuel Option, 7-Day Programmable, Backlit, 24 Volt, Auto Changeover, System Switch – Heat, Off, Cool, Emergency, Auto, Fan Switch – Auto, On, Program Fan, EMR, Keypad Lockout, Profile – Horizontal, Hardwire, Range 45-99°F, Terminals – RC, RH, C, G, Y, Y2, W/E, W2, O/B, L, +, S, -, 6, DHM, DHM2, HM, HM2. |



1F85-0477



1F95-1277



1F95-0680



1F95EZ-0671



1F95-1291


 1F98EZ-1441
 includes User Interface,
 Equipment Control and
 Outdoor Remote Sensor
 (F145-1378)

(cont'd on next page)

WHITE-RODGERS CONTROLS

www.white-rodgers.com

THERMOSTATS (cont'd)

UNIVERSAL PROGRAMMABLE (cont'd)

| ITEM # | MODEL | DESCRIPTION |
|--------|-------------|--|
| 751556 | 1F98EZ-1621 | Blue Wireless Easy Install 6" Display, Universal Single Stage, Multi-Stage, Heat-Pump up to (4H/2C), with Humidification/Dehum, 7-Day Program, Backlit, Auto Changeover, Dual Fuel (requires sensor below), System Switch – Heat, Off, Cool, Emergency, Auto, Fan Switch – Auto, On, EMR, Keypad Lockout, Profile – Horizontal, Range 45-99°F, Module Terminals – RC, RH, C, G, Y, Y2, W/E, W2, O/B, L, DHM, DHM2, HM, HM2. Compatible with F145RF-1600 Indoor/Outdoor Wireless Temperature Sensor, sold separately. |



1F98EZ-1621



Equipment Control Module

UNIVERSAL NON-PROGRAMMABLE

| ITEM # | MODEL | DESCRIPTION |
|--------|-------------|--|
| 751546 | 1F83-0471 | 80 Series Blue Universal Single Stage, Multi-Stage (2H/2C) or Heat Pump (3H/2C). Non-Programmable Digital Thermostat, Backlit Display, 24 Volts or Millivolt, System Switch – Heat, Off, Cool, Auto, Emer., Fan Switch – Auto, On, Profile – Horizontal, Dual Power (R-C) and/or Batteries, Range 45-90°F. Terminals – RC, RH, C, G, W/E, W2, Y, Y2, O/B/6, L. Includes F61-2634 Wall Plate. |
| 751554 | 1F89EZ-0251 | Blue 2" Display, Heat Pump (2H/1C) Non-Programmable Digital Thermostat, Home-Sleep-Away buttons. Backlit Display, 24 Volts, System Switch-Heat, Off, Cool, Emer. Auto, Fan Switch-Auto, On, Profile – Horizontal, Dual Power (System and/or Battery), Range 45-90°F, Terminals – R, C, G, Y, W2, O/B, L. |



1F83-0471



1F89-0251

REMOTE SENSORS

| ITEM # | MODEL | DESCRIPTION |
|--------|-----------|---|
| 751240 | F145-1328 | Indoor Remote Sensor, compatible with all White-Rodgers Thermostats with Indoor Remote Sensor Option. |
| 751244 | F145-1378 | Outdoor Remote Sensor, compatible with all White-Rodgers Thermostats with Outdoor Remote Sensor Option, can be used in dual fuel installations with 1F95 etc. |



F145-1328



F145-1378

GUARDS

| ITEM # | MODEL | DESCRIPTION |
|--------|----------|---|
| 751028 | F29-0143 | Thermostat Guard, Transparent Cover with Mounting Plate and Mounting Ring, fits 1C20, 1C21, 1C26, 1C30, 1D30, 1D36, 1D56, 1E30, 1E31, 1E35, 1E56, 1F30, 1F35, 1F36, 1F51, 1F56, 1F57, 1F58. |
| 751038 | F29-0192 | Steel Thermostat Guard with Solid Base (Hinged), Fits 1C20, 1C21, 1C26, 1C30, 1D30, 1D36, 1D56, 1E30, 1E31, 1E35, 1E56, 1E78, 1F30, 1F35, 1F36, 1F51, 1F56, 1F57, 1F58, 1F72, 1F73, 1F78, 1F79. |
| 751044 | F29-0198 | Universal Thermostat Guard, Clear Cover, with Mounting Plate and Mounting Ring for use with all White-Rodgers Room Thermostats including "Blue" |
| 751050 | F29-0220 | Universal Size Steel Thermostat Guard, with Solid Mounting Plate for use with all White-Rodgers Room Thermostats including "Blue". |



F29-0192



F29-0198

(cont'd on next page)

WHITE-RODGERS CONTROLS

www.white-roddgers.com

THERMOSTATS (cont'd)

GUARDS (cont'd)

| ITEM # | MODEL | DESCRIPTION |
|--------|-----------|--|
| 751052 | F29-0231 | Clear Plastic Thermostat Guard for use with 1F90, 1F97 Series Thermostats for use with all White-Rodgers Room Thermostats except "Blue". |
| 751250 | F145-0999 | Key for Thermostat Guards (All) |



F29-0231


 S29-21
(SUBBASE WITH
1A10-651
THERMOSTAT)

SUBBASE

| ITEM # | MODEL | DESCRIPTION |
|--------|--------|--|
| 708368 | S29-21 | Subbases For Use With 1A10-651 Or 1A16-51 Line Voltage Thermostats, System Switch: Cool-Off-Heat, Replaces S29-1 |

WALL PLATES

| ITEM # | MODEL | DESCRIPTION |
|--------|----------|--|
| 751526 | F61-2593 | Wall Plate for 1D70 or 1E70 Series Thermostats, 4-1/2"W x 6-19/32"H, Classic White Color. |
| 751528 | F61-2634 | Wall Plate for 90 and 80 Series Blue Thermostats, 6-1/2"W x 5"H, Classic White Color, for use with or without Horizontal Junction Box. |



F61-2593

UV ZONING

| ITEM # | MODEL | DESCRIPTION |
|--------|--------|--|
| 751972 | 2070-5 | Zone Air Control. Motor – 2 wire, open in 30 seconds, close in 20 seconds, 0.35A @ 24VAC, used for solid fuels, with mounting plate 61-1970. |



SERVICE PARTS

| ITEM # | MODEL | DESCRIPTION |
|--------|------------|--|
| 810241 | 38-2206-01 | Thrust Collar Kit, 3/4" |
| 810243 | 38-2491-02 | Thrust Spacer Kit, 3/4" (12 spacers per pack) |
| 810245 | 38-2209-01 | Vibro Pads (12 per pack) |
| 810247 | 38-2525-01 | Motor Adjustment Grommets (6 per pack) |



38-2206-01



38-2491-02



38-2525-01

CONTROLS

SNAP DISC

| ITEM # | MODEL | DESCRIPTION |
|--------|----------|---|
| 751600 | 3F01-45 | Close on rise, 45°F (7.2°C) cut-in / 35°F (1.7°C) Cut-Out Settings, 10A @ 120VAC / 5A @ 240VAC FL, 25A @ 120/240VAC / 21.6A @ 277V Non-Inductive, 125VA pilot duty. |
| 751602 | 3F01-110 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Close on Rise, 110°F Cut-In Temperature, 20°F Differential. Therm-O-Disc Style 60T12, Type 610044. |



3F01-110

(cont'd on next page)

WHITE-RODGERS CONTROLS

www.white-roddgers.com

CONTROLS (cont'd)

SNAP DISC (cont'd)

| ITEM # | MODEL | DESCRIPTION |
|--------|----------|---|
| 751604 | 3F01-120 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Close on Rise, 120°F Cut-In Temperature, 10°F Differential. Therm-O-Disc Style 60T12, Type 610046. |
| 751606 | 3F01-130 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Close on Rise, 130°F Cut-In Temperature, 15°F Differential. Therm-O-Disc Style 60T12, Type 610047. |
| 751610 | 3F01-140 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Close on Rise, 140°F Cut-In Temperature, 20°F Differential. Therm-O-Disc Style 60T12, Type 610049. |
| 751612 | 3F01-150 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Close on Rise, 150°F Cut-In Temperature, 20°F Differential. Therm-O-Disc Style 60T12, Type 610050. |
| 751614 | 3F01-160 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Close on Rise, 160°F Cut-In Temperature, 20°F Differential. Therm-O-Disc Style 60T12, Type 610064. |
| 751616 | 3F01-180 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Close on Rise, 180°F Cut-In Temperature, 20°F Differential. Therm-O-Disc Style 60T12, Type 610065. |
| 751618 | 3F01-200 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Close on Rise, 200°F Cut-In Temperature, 20°F Differential. Therm-O-Disc Style 60T12, Type 610066. |



SNAP DISC AND FAN LIMIT — ADJUSTABLE

| ITEM # | MODEL | DESCRIPTION |
|--------|--------|---|
| 751628 | 3F05-1 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Close on Rise, Adjustable Set Point, Range 90°F to 130°F, 20°F Diff, Auto Reset. Therm-O-Disc Style 74T12, Type 310708. |
| 751629 | 3F05-2 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Close on Rise, Adjustable Set Point, Range 140°F to 180°F, 20°F Diff, Auto Reset. Therm-O-Disc Style 74T12, Type 310709. |
| 751676 | 3L05-1 | Snap Disc Limit Control, SPST, Flanged Airstream Mount, Open on Rise, Adjustable Set Point, 135°F to 175°F Range, 40°F Diff, Auto. Reset. Therm-O-Disc Style 74T11, Type 310710. |



SNAP DISC AND FAN LIMIT

| ITEM # | MODEL | DESCRIPTION |
|--------|----------|--|
| 751630 | 3L01-120 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Open on Rise, 120°F Cut-Out Temperature, 10°F Differential. Therm-O-Disc Style 60T11, Type 610000 |
| 751634 | 3L01-130 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Open on Rise, 130°F Cut-Out Temperature, 15°F Differential. Therm-O-Disc Style 60T11, Type 610002 |
| 751636 | 3L01-140 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Open on Rise, 140°F Cut-Out Temperature, 40°F Differential. Therm-O-Disc Style 60T11, Type 610006 |
| 751638 | 3L01-150 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Open on Rise, 150°F Cut-Out Temperature, 40°F Differential. Therm-O-Disc Style 60T11, Type 610009 |



(cont'd on next page)

CONTROLS (cont'd)
SNAP DISC AND FAN LIMIT (cont'd)

| ITEM # | MODEL | DESCRIPTION |
|--------|----------|--|
| 751640 | 3L01-160 | Open on rise, 120°F (49°C) cut-in / 160°F (72°C) Cut-Out Settings, 10°F (5.6°C) Differential, 10A @ 120VAC / 5A @ 240VAC FL, 25A @ 120/240VAC / 21.6A @ 277V Non-Inductive, 125VA Pilot Duty |
| 751642 | 3L01-170 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Open on Rise, 170°F Cut-Out Temperature, 40°F Differential. Therm-O-Disc Style 60T11, Type 610012 |
| 751644 | 3L01-180 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Open on Rise, 180°F Cut-Out Temperature, 40°F Differential. Therm-O-Disc Style 60T11, Type 610013 |
| 751646 | 3L01-190 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Open on Rise, 190°F Cut-Out Temperature, 40°F Differential. Therm-O-Disc Style 60T11, Type 610015 |
| 751648 | 3L01-200 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Open on Rise, 200°F Cut-Out Temperature, 40°F Differential. Therm-O-Disc Style 60T11, Type 610016 |
| 751650 | 3L01-230 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Open on Rise, 230°F Cut-Out Temperature, 40°F Differential. Therm-O-Disc Style 60T11, Type 610021 |
| 751652 | 3L01-250 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Open on Rise, 250°F Cut-Out Temperature, 40°F Differential. Therm-O-Disc Style 60T11, Type 610023 |
| 751654 | 3L01-300 | Snap Disc Fan Control 3/4" SPST Flanged Airstream Mount, Open on Rise, 300°F Cut-Out Temperature, 50°F Differential. Therm-O-Disc Style 60T11, Type 610026 |
| 751660 | 3L02-160 | Snap Disc Limit Control 3/4" SPST Flanged Airstream Mount, Open on Rise, 160°F Cut-Out Temperature Manual Reset. Therm-O-Disc Style 60T15, Type 330534 |
| 751664 | 3L02-180 | Snap Disc Limit Control 3/4" SPST Flanged Airstream Mount, Open on Rise, 180°F Cut-Out Temperature Manual Reset. Therm-O-Disc Style 60T15, Type 330536 |
| 751666 | 3L02-190 | Snap Disc Limit Control 3/4" SPST Flanged Airstream Mount, Open on Rise, 190°F Cut-Out Temperature Manual Reset. Therm-O-Disc Style 60T15, Type 330537 |
| 751668 | 3L02-200 | Snap Disc Limit Control 3/4" SPST Flanged Airstream Mount, Open on Rise, 200°F Cut-Out Temperature Manual Reset. Therm-O-Disc Style 60T15, Type 330538 |
| 751670 | 3L03-140 | Snap Disc Limit Control 3/4" SPDT Flanged Airstream Mount, Open on Rise, 140°F Cut-Out, 20°F Differential. Therm-O-Disc Style 60T13, Type 611015 |
| 751672 | 3L03-190 | Snap Disc Limit Control 3/4" SPDT Flanged Airstream Mount, Open on Rise, 190°F Cut-Out, 20°F Differential. Therm-O-Disc Style 60T13, Type 611014 |
| 751673 | 3L05-2 | Snap Disc Limit Control, SPST Flanged Airstream Mount, Open on Rise, Adjustable Set Point, 175°F – 215°F Range, 40°F Differential, Auto Reset. Therm-O-Disc Style 74T11, Type 310711 |
| 751674 | 3L05-3 | Snap Disc Limit Control, SPST Flanged Airstream Mount, Open on Rise, Adjustable Set Point, 210°F – 250°F Range, 40°F Differential, Auto Reset. Therm-O-Disc Style 74T11, Type 310712 |



3L01-180



3L02-180



3L03-140



3L02-190

WHITE-RODGERS CONTROLS

www.white-roddgers.com

CONTROLS (cont'd)

REFRIGERATION — LIQUID LINE FILTER DRIERS

| ITEM # | MODEL | DESCRIPTION |
|--------|-----------|---|
| 751166 | 96-TD032 | Liquid Line Filter Drier, 1/4" SAE (L" x W") 4.32" x 1.63", Flow Capacity (ARI STD 710.86) Tons @ 1 PSI Delta P Refrigerant 134a=1.2, R-22=1.9, R-404a/R507=1.2 |
| 751162 | 96-TD032S | Liquid Line Filter Drier, 1/4" ODF – 3/8 ODM (L" x W") 3.76" x 1.63", Flow Capacity (ARI STD 710.86) Tons @ 1 PSI Delta P Refrigerant 134a=2.1, R-22=2.2, R-404a/R507=1.5 |
| 751168 | 96-TD052 | Liquid Line Filter Drier, 1/4" SAE (L" x W") 4.88" x 2.5", Flow Capacity (ARI STD 710.86) Tons @ 1 PSI Delta P Refrigerant 134a=1.8, R-22=2, R-404a/R507=1.3 |
| 751164 | 96-TD052S | Liquid Line Filter Drier, 1/4" ODF (L" x W") 4.33" x 2.5", Flow Capacity (ARI STD 710.86) Tons @ 1 PSI Delta P Refrigerant 134a=2.6, R-22=2.8, R-404a/R507=1.9 |
| 751158 | 96-TD053S | Liquid Line Filter Drier, 3/8" ODF (L" x W") 4.53" x 2.5", Flow Capacity (ARI STD 710.86) Tons @ 1 PSI Delta P Refrigerant 134a=4.1, R-22=4.4, R-404a/R507=2.9 |
| 751170 | 96-TD082S | Liquid Line Filter Drier, 1/4" ODF (L" x W") 5.24" x 2.5", Flow Capacity (ARI STD 710.86) Tons @ 1 PSI Delta P Refrigerant 134a=2.8, R-22=3, R-404a/R507=2.0 |
| 751161 | 96-TD083S | Liquid Line Filter Drier, 3/8" ODF (L" x W") 5.43" x 2.5", Flow Capacity (ARI STD 710.86) Tons @ 1 PSI Delta P Refrigerant 134a=3.8, R-22=4.1, R-404a/R507=2.7 |
| 751192 | 96-TD163 | Liquid Line Filter Drier, 3/8" SAE (L" x W") 6.89" x 2.5", Flow Capacity (ARI STD 710.86) Tons @ 1 PSI Delta P Refrigerant 134a=4.0, R-22=4.3, R-404a/R507=2.9 |
| 751194 | 96-TD163S | Liquid Line Filter Drier, 3/8" ODF (L" x W") 6.22" x 2.5", Flow Capacity (ARI STD 710.86) Tons @ 1 PSI Delta P Refrigerant 134a=4.4, R-22=4.8, R-404a/R507=3.2 |
| 751178 | 96-TD303S | Liquid Line Filter Drier, 3/8" ODF (L" x W") 8.9" x 3", Flow Capacity (ARI STD 710.86) Tons @ 1 PSI Delta P Refrigerant 134a=5.7, R-22=6.1, R-404a/R507=4.1 |
| 751180 | 96-TD304S | Liquid Line Filter Drier, 1/2" ODF (L" x W") 8.94" x 3", Flow Capacity (ARI STD 710.86) Tons @ 1 PSI Delta P Refrigerant 134a=7.9, R-22=8.6, R-404a/R507=5.7 |
| 751210 | 96-TD305S | Liquid Line Filter Drier, 5/8" ODF (L" x W") 9.21" x 3", Flow Capacity (ARI STD 710.86) Tons @ 1 PSI Delta P Refrigerant 134a=13.1, R-22=14.1, R-404a/R507=9.5 |



96-TD

REFRIGERATION — TEMPERATURE

| ITEM # | MODEL | DESCRIPTION |
|--------|-----------|--|
| 752020 | 16E09-101 | Switch; SPDT; Range: -40°F to 220°F (-40°C to 104°C); Diff.: 1° to 30°F and C; Temperature Sensor Lead Length: 7-1/2 FT. |
| 751950 | 1687-9 | SPDT, -30°F to 90°F Range, 4-1/2°F to 40°F Adjustable Differential, 8' Capillary |


 16E09-101
with Sensor


1687-9

WHITE-RODGERS CONTROLS

www.white-roddgers.com

CONTROLS (cont'd)

REFRIGERATION — DRIERS — SUCTION LINE

| ITEM # | MODEL | DESCRIPTION |
|--------|-----------|---------------------------------|
| 751196 | 96-TS165S | 5/8" ODF (L" x W") 6.54" x 2.5" |
| 751197 | 96-TS166S | 3/4" ODF (L" x W") 6.95" x 2.5" |
| 751198 | 96-TS167S | 7/8" ODF (L" x W") 7.13" x 2.5" |



96-TS

REFRIGERATION — DRIERS — BI-DIRECTIONAL HEAT PUMP

| ITEM # | MODEL | DESCRIPTION |
|--------|------------|---|
| 751176 | 96-TBF163S | Bi-Directional Heat Pump Drier, 3/8" ODF, 6.31" x 2.63" |
| 751200 | 96-TBF163 | Bi-Directional Heat Pump Drier, 3/8" SAE, 6.97" x 2.63" |
| 751204 | 96-TBF165S | Bi-Directional Heat Pump Drier, 5/8" ODF, 6.63" x 3.09" |



96-TBF

REFRIGERATION — MOISTURE INDICATORS

| ITEM # | MODEL | DESCRIPTION |
|--------|------------|-----------------------------------|
| 751208 | 96-HMIY3SS | 3/8" Sweat x Sweat, 4.57" x 1.11" |

BURNOUT CLEAN-UP FILTER DRIER

| ITEM # | MODEL | DESCRIPTION |
|--------|----------|---|
| 751186 | 96-W48HH | Burnout Clean-Up Filter Drier Core Replacement, 48 Cubic Inches |

WARM AIR — FAN AND LIMIT

| ITEM # | MODEL | DESCRIPTION |
|--------|---------|---|
| 751704 | 5D51-35 | Fan: 50°F to 265°F Range, Adjustable Differential, Limit: 100°F to 300°F Range, 25°F Fixed Differential, 5" Element, Adjustable Limit Stop, Summer Fan Switch, Standard Enclosure, No Mounting Bracket, Line Voltage Jumper. |
| 751706 | 5D51-78 | Fan: 50°F to 265°F Range, Adjustable Differential, Limit: 100°F to 300°F Range, 25°F Fixed Differential, 11" Element, Adjustable Limit Stop, Summer Fan Switch, Standard Enclosure, No Mounting Bracket, Line Voltage Jumper. |
| 751710 | 5D51-90 | Fan: 50°F to 265°F Range, Adjustable Differential, Limit: 100°F to 300°F Range, 25°F Fixed Differential, 8" Element, Adjustable Limit Stop, Summer Fan Switch, Standard Enclosure, No Mounting Bracket, Line Voltage Jumper. |



5D51-35

BOARD MOUNT LIMIT

| ITEM # | MODEL | DESCRIPTION |
|--------|---------|--|
| 751680 | 3L09-7 | 1/2" Bimetal Disc, Opens at 175°F, Closes at 145°F, Length 3.12" Therm-O-Disc Style 612711, Type 36T |
| 751681 | 3L09-8 | 1/2" Bimetal Disc, Opens at 180°F, Closes at 160°F, Length 3.12" Therm-O-Disc Style 612714, Type 36T |
| 751682 | 3L09-9 | 1/2" Bimetal Disc, Opens at 190°F, Closes at 170°F, Length 3.12" Therm-O-Disc Style 612715, Type 36T |
| 751683 | 3L09-10 | 1/2" Bimetal Disc, Opens at 200°F, Closes at 160°F, Length 3.12" Therm-O-Disc Style 612718, Type 36T |
| 751685 | 3L09-19 | 1/2" Bimetal Disc, Opens at 175°F, Closes at 145°F, Length 7.12" Therm-O-Disc Style 612712, Type 36T |



3L09

- E.&O.E. - All Prices F.O.B. Our Warehouse - Subject to Change Without Notice - All Taxes Extra - May not be Available at All Branches -

WHITE-RODGERS CONTROLS

www.white-rodders.com

CONTROLS (cont'd)

FURNACE CONTROL KITS

| ITEM # | MODEL | DESCRIPTION |
|--------|------------|--|
| 752006 | 21D64-2 | 120V Silicon Nitride Upgrade Kit for Conversion of Silicon Carbide (flat or spiral) includes, 2 Brackets, Furnace label, Instruction booklet, and 2 Ceramic wire nuts. Does NOT require power adapter module. |
| 752424 | 21D83M-843 | Universal Hot Surface Ignition Integrated Furnace Control. Includes 21D64-2 Universal Ignitor. |



21D64-2



21D83M-843

MISCELLANEOUS

| ITEM # | MODEL | DESCRIPTION |
|--------|---------|---|
| 751756 | 760-401 | Standard Replacement Sense Electrode, 30" Lead Length, 1/4" Female Spade Terminal |



760-401

IGNITION COMPONENTS

| ITEM # | MODEL | DESCRIPTION |
|--------|------------|---|
| 752368 | 5059-23 | Pilot Relite Control, 1/4" Spade Terminals, 24V Input, 1/4" Spade Terminal High Voltage Connection |
| 752400 | 50A55-743 | Drop In Direct Replacement Ignition Control for Goodman PCBBF123 and White-Rodgers 50T55-289 – Silicon Carbide Single Stage Furnace Control carbide Single Stage Furnace Control |
| 752372 | 50A65-843 | Universal Silicon Nitride (Hot Surface) Ignition Control with Variable Timings. Replaces 50A65-120, -143, -288, -474, -475 and more. |
| 752392 | 50A55-843 | Universal Silicon Carbide Integrated Ignition Control (Hot Surface Ignition). Replaces 50A50/50A55-143, -285, -286, -288, -438, -571, -474 and more. |
| 752380 | 50D50-842 | Universal Direct Spark Ignition Control with Variable Timings |
| 752382 | 50D50-843 | Universal Proven Pilot Spark Ignition Control with Variable Timings. Replaces Honeywell S8610U1003 and other Controls |
| 752408 | 50E47-843 | Universal Hot Surface Ignition Control with Variable Timings. Replaces 50E47-30, -50, -60, -70, -130, -140, -150, 160, -170, -850, -851, many other models and many competitive controls. |
| 752412 | 50M56U-843 | Universal Hot Surface Ignition Integrated Furnace Control. Includes 21D64-2 Universal Ignitor. |
| 752420 | 50T35-743 | Replacement Ignition Control For Goodman B1809913, UTEC 1012-933D, TI 41F-5, White-Rodgers 50T35-730. |



5059-23



50A55-743



50A55-843



50D50-842



50D50-843



50M56U-843



50E47-843



50T35-743

- E.&O.E. - All Prices F.O.B. Our Warehouse - Subject to Change Without Notice - All Taxes Extra - May not be Available at All Branches -

WHITE-RODGERS CONTROLS


www.white-roddgers.com

CONTROLS (cont'd)

FURNACE — HOT SURFACE IGNITORS — SILICONE CARBIDE

| ITEM # | MODEL | DESCRIPTION |
|--------|----------|--|
| 751788 | 767A-361 | Hot Surface Ignitor with 5.25" Leads, 250° Insulation, Electrical Connection Receptacle with .093" Male Pins. Replaces R/S 41-405 |
| 751760 | 767A-369 | Hot Surface Ignitor with 5-1/2" Leads, A Style Mounting Block, Sealed Combustion, Insulation 200°C, Amp Terminal Connection, includes Gasket. Replaces R/S 41-401 |
| 751762 | 767A-370 | Hot Surface Ignitor with 5-1/4" Leads, M Style Mounting Block, Insulation 200°C, Stripped Ends. Replaces R/S 41-403, 41-409 |
| 751764 | 767A-371 | Hot Surface Ignitor with 19-1/8": Leads, W Style Mounting Block, Left Tab, Insulation 200°C, Stripped Ends, Replaces R/S 41-402 |
| 751763 | 767A-372 | Hot Surface Ignitor with 5-1/4" Leads, N Style Mounting Block, Left Tab, Insulation 200°C, Stripped Ends, Replaces R/S 41-408, and 41-411 |
| 751765 | 767A-373 | Hot Surface Ignitor with 5-1/4" Leads, NM Style Mounting Block, right tab, Insulation 200°C, Amp Terminal Connector, includes Ceramic Wire Nuts. Replaces R/S 41-412, 41-414 |
| 751766 | 767A-374 | Hot Surface Ignitor with 11" leads, Y Style Mounting Block, Oblong Base, Insulation 200°C, Stripped Ends, includes Ceramic Wire Nuts, includes Gasket. Replaces R/S 41-406 |
| 751789 | 767A-375 | Hot Surface Ignitor with 1-3/8" leads, 270°C Mounting Block, Cylinder Base, Insulation 200°C, 1/4" Spade Terminals, includes Ceramic Wire Nuts. Replaces R/S 41-413 |
| 751790 | 767A-376 | Hot Surface Ignitor with 4-1/2" Leads, G Style Mounting Block, Insulation 200°C, Amp Terminal Connector, includes Ceramic Wire Nuts. Replaces R/S 41-407 |
| 751791 | 767A-377 | Hot Surface Ignitor with 4-1/2" Leads, N Style Mounting Block, Insulation 200°C, Amp Terminal Connector, includes Ceramic Wire Nuts. Replaces R/S 41-410 |
| 751767 | 767A-378 | Hot Surface Ignitor Mini with 5.125" (+/- .5") Leads including Electrical Connector. Replaces R/S 41-602, 41-603, Amana 201657-03S, Goodman 601, and Goodman 0230K00001 conversion kit |
| 751769 | 767A-379 | Hot Surface Ignitor Mini with 7.5" (+/- 1") Leads including Electrical Connector. Replaces R/S 41-603 |
| 751784 | 767A-380 | Hot Surface Ignitor Mini with 6.125" (+/- .5") Leads including Electrical Connector. Replaces R/S 41-604 |
| 751770 | 767A-381 | Hot Surface Ignitor Mini with 7.5" (+/- 1") Leads including Electrical Connector. Includes Mounting Adaptor. Replaces R/S 41-605 |
| 751768 | 767A-382 | Hot Surface Ignitor with 5-1/4" Leads, M Style Mounting Block, Insulation 200°C, Connector with Mounting Adaptor, Replaces R/S 41-404 |
| 751792 | 767A-383 | Hot Surface Ignitor with 5-1/4" Leads, N Style Mounting Block, Left Tab, Insulation 200°C, Connector with Mounting Adaptor, Replaces R/S 41-411 |

(cont'd on next page)



767A-361



767A-369



767A-370




767A-371



767A-372



767A-373



767A-374



767A-375



767A-376



767A-377




767A-378




767A-379



767A-380



767A-381



767A-382



767A-383

WHITE-RODGERS CONTROLS

www.white-roddgers.com

CONTROLS (cont'd)

FURNACE — HOT SURFACE IGNITORS — SILICONE CARBIDE (cont'd)

| ITEM # | MODEL | DESCRIPTION |
|--------|----------|--|
| 751793 | 767A-384 | Hot Surface Ignitor with 5-1/4" Leads, NM Style Mounting Block, right tab, Insulation 200°C, Connector with Brackets, includes Ceramic Wire Nuts. Replaces R/S 41-414 |
| 751780 | 768A-815 | Silicon Nitride 80V Hot Surface Ignitor, with White Teflon Coated Leads, Steatite Insulator with Steel Zinc Plated Mounting Tab, 2 Terminal Amp Receptacle with .084" Female Socket, Must Be Used with Hot Surface Ignition for Residential Furnaces (Silicon Nitride Replacement Only) Replaces Trane 768A-15 (A341947P01) |
| 751775 | 768A-842 | Silicon Nitride Hot Surface Ignitor with 55 Mm White Teflon Coated Leads, Steatite Insulator with Steel Zinc Plated Mounting Tabs, 2 Terminal Amp Receptacle with .093 Female Socket, Must Be Used with Hot Surface Ignition for 120V Residential Furnaces (Silicon Nitride Replacement Only) Replaces Amana 768A-2 |
| 751778 | 768A-843 | Silicon Nitride Hot Surface Ignitor with 55 Mm Ignitor White Teflon Coated Leads, Steatite Insulator with Steel Zinc Plated Mounting Tab, 2 Terminal Amp Receptacle with .084" Female Socket, Must Be Used with Hot Surface Ignition for 120V Residential Furnaces (Silicon Nitride Replacement Only) , Replaces Thermo 768A-143 |
| 751781 | 768A-844 | Silicon Nitride Hot Surface Ignitor with 55 Mm Ignitor White Teflon Coated Leads, Steatite Insulator with Zinc Plated Mounting Tab, 2 Terminal Amp Receptacle with .084" Female Socket, Must Be Used with Hot Surface Ignition for 120V Residential Furnaces (Silicon Nitride Replacement Only) Replaces Lennox 768A-4 |
| 751779 | 768A-845 | Silicon Nitride Hot Surface Ignitor with 54mm White Teflon Coated Leads, Steatite Insulator, 2 Terminal AMP Receptacle with .084" Female Socket, Must Be Used with Hot Surface Ignition for 120V Residential Furnaces (Silicon Nitride Replacement Only) Replaces Trane 768A-5 |



767A-384



768A-815



768A-842



768A-843



768A-844



768A-845

OIL AND GAS BURNER

| ITEM # | MODEL | DESCRIPTION |
|--------|----------|--|
| 752133 | 3049-115 | Mercury Flame Sensor, 48" Element, Two 1/4" Spade Terminals, One Pin Terminal, Bulb Style #20 |
| 752134 | 3098-134 | Mercury Flame Sensor, 48" Element, 3 Pin Plug, Bulb Style #19. Replaces 3098-111, 3098-136, 3098-141, 3098-147, 3098-161, 3098-165, 3098-169, 3098-184 |



3098-134

OIL AND GAS BURNER — UNIVERSAL THERMOCOUPLES

| ITEM # | MODEL | DESCRIPTION |
|--------|---------|-------------------------|
| 752008 | H06E-18 | 18" Thermocouple, 30 mV |
| 752010 | H06E-24 | 24" Thermocouple, 30 mV |
| 752012 | H06E-30 | 30" Thermocouple, 30 mV |
| 752014 | H06E-36 | 36" Thermocouple, 30 mV |
| 752016 | H06E-48 | 48" Thermocouple, 30 mV |



H06E

WHITE-RODGERS CONTROLS

www.white-rodders.com

CONTROLS (cont'd)

OIL AND GAS BURNER — MILLIVOLT POWER GENERATORS

| ITEM # | MODEL | DESCRIPTION |
|--------|----------|---|
| 752600 | G01A-132 | S2, 750 mV, 36" leads, armored cable, PG9 adapter, split-spade terminals, for use with E31-12 pilot burner. |



HYDRONIC

| ITEM # | MODEL | DESCRIPTION |
|--------|---------|---|
| 751866 | 11B06-1 | Remote Bulb Hydronic Control, SPST, Open on Rise, 100°F to 240°F Range, 5°F to 45°F Adjustable Differential, 5' Capillary |

AIR SWITCH — DUAL PURPOSE

| ITEM # | MODEL | DESCRIPTION |
|--------|-------|--|
| 751794 | 770-3 | SPDT, 0.07" to 12" W.C. Operating Range, -40°F to +180°F (-40° C to 82°C) Ambient Temperature, 15A @ 120/240/277VAC non-inductive, 300VA pilot duty, furnished with one 6" piece 1/4" O.D. flexible tubing, nuts and ferrules. |



CONTACTORS

| ITEM # | MODEL | DESCRIPTION |
|--------|--------|--|
| 751120 | 90-163 | 3 Pole, 24VAC Coil, 30 Amp Contacts, 7.2 Ohms DC Resistance, 187mA, 4.5VA (Nominal), Maximum 52VA (Inrush) |
| 751121 | 90-164 | 3 Pole, 120VAC Coil, 30 Amp Contacts, 180 Ohms DC Resistance, 37mA, 4.5VA (Nominal), Maximum 52VA (Inrush) |
| 751122 | 90-165 | 3 Pole, 208/240VAC Coil, 30 Amp Contacts, 720 Ohms DC Resistance, 19mA, 4.5VA (Nominal), Maximum 52VA (Inrush) |
| 751124 | 90-170 | 3 Pole, 24VAC Coil, 40 Amp Contacts with Dust Cover, 7.2 Ohms DC Resistance, 187mA, 4.5VA (Nominal), Maximum 52VA (Inrush) |
| 751125 | 90-171 | 3 Pole, 120VAC Coil, 40 Amp Contacts with Dust Cover, 180 Ohms DC Resistance, 37mA, 4.5VA (Nominal), Maximum 52 VA (Inrush) |
| 751126 | 90-172 | 3 Pole, 208/240VAC Coil, 40 Amp Contacts with Dust Cover, 720 Ohms DC Resistance, 19mA, 4.5VA (Nominal), Maximum 52VA (Inrush) |
| 751128 | 90-244 | 2 Pole, Type 122, 24VAC Coil, 30 Amp Contacts, 11 Ohms DC Resistance, 250mA, 6VA (Nominal), Maximum 32VA (Inrush) |
| 751127 | 90-245 | 2 Pole, Type 122, 120 VAC Coil, 30 Amp Contacts, 224 Ohms DC Resistance, 50 mA, 6 VA (Nominal), Maximum 32VA (Inrush) |
| 751129 | 90-247 | 2 Pole, Type 122, 24 AC Coil, 40 Amp Contacts, 11 Ohms DC Resistance, 250mA, 6VA (Nominal), Maximum 32VA (Inrush) |



90-163 to 90-172



90-244



90-245



90-247

WHITE-RODGERS CONTROLS

www.white-roddgers.com

GAS VALVES

| ITEM # | MODEL | DESCRIPTION |
|--------|------------|---|
| 752216 | 36C03-258 | Standing Pilot, fast opening, Nat, 230,000 BTU, 3.5"W.C., 1/2" x 1/2" inlet/outlet size, 24VAC, 60Hz, line interrupter, has ECO terminals, for use with thermocouple H06E series. Same as 36C03-433 model, c/w 1/2" bushing. |
| 752218 | 36C03-300 | Gas Valve, 1/2" x 3/4", 24 VAC, Thermocouple Actuated Line Interrupter, Reducer Bushings (3/4" to 1/2" and 1/2" to 3/8"), includes LP Conversion Kit, ECO Terminals |
| 752219 | 36C03-333 | Universal Gas Valve, 1/2" x 3/4", 24 VAC, Side Outlets Tapped and Plugged, Thermocouple Actuated Line Interrupter, Reducer Bushings (3/4" to 1/2" and 1/2" to 3/8"), includes LP Conversion Kit, ECO Terminals |
| 752224 | 36C03-433 | Universal Gas Valve, 3/4" x 3/4", 24VAC, Side Outlets Tapped and Plugged, Thermocouple Actuated Line Interrupter, Reducer Bushings (Two 3/4" to 1/2"), includes LP Conversion Kit, ECO Terminals. Same as 36C03-258 |
| 752230 | 36C03A-410 | Gas Valve, 3/4" x 3/4", 120 VAC, Thermocouple Actuated Line Interrupter, includes LP Conversion Kit, Reducer Bushings, Side Taps, Eco Terminals |
| 752228 | 36C03U-433 | Universal Gas Valve, 3/4" x 1/2", 750 Mv, Side Outlets Tapped and Plugged, Reducer Bushings, (Two 3/4" to 1/2"), includes LP Conversion Kit, ECO Terminals – Universal version of -258 |
| 752234 | 36C53-418 | Gas Valve, 3/4" x 3/4", 24 VAC, Thermocouple Actuated Line Interrupter, ECO Terminals with Jumper Lead, Slow Opening, Reducer Bushings, Blocking Pin LP Kit, No Side Taps |
| 752277 | 36C74-913 | Gas Valve, 3/4" x 3/4", 24 VAC, 0.9" Step, 3.5" Full Outlet Pressure, Plugged Pilot, Reducer Bushings, 1/4" Pilot Fitting, Two 42" Extra Leads, Natural Gas Only |
| 752282 | 36C84-912 | Gas Valve, 3/4" x 3/4", 24 VAC, Redundant (Pilot) Valve, Fast Opening, 1/4" Pilot Fitting, LP Kit, 2 Each Extra Jumpers and 30" Leads, Plug In Pilot Socket on Outlet Side, Reducer Bushings, 1/4" Quick Connect Terminals (C, C, L, S) |
| 752281 | 36C84-921 | Gas Valve, 3/4" x 3/4", 24 VAC, Redundant (Pilot) Valve, Fast Opening, 1/4" Pilot Fitting, LP Kit, 2 Each Extra Jumpers and 30" Leads, Plug In Pilot Socket on Top, Reducer Bushings, 1/4" Quick Connect Terminals (C, C, L, S) |
| 752280 | 36C84-926 | Gas Valve, 3/4" x 3/4", 24VAC, Redundant (Pilot) Valve, Fast Opening, 1/4" Pilot Fitting, Plug In Pilot Socket On Outlet Side, Reducer Bushings, Edge Connector to PC Board, No LP Kit. Use with 3098 Type Mercury Flame Sensor, F115-0064 Wiring Harness. |
| 752284 | 36C84-945 | Gas Valve, 3/4" x 3/4", 24 VAC, Redundant (Pilot) Valve, Fast Opening, 1/4" Pilot Fitting, Reducer Bushings, LP Kit, Three 1/4" Spade Terminals and One 5/16" Diameter Pin Terminal, One 24" Lead with Barrel and 1/4" |
| 752239 | 36C94-906 | Gas Valve, 3/4" x 3/4", 24 VAC, Redundant (Pilot) Valve, 1/4" Pilot Fitting, LP Kit, Plug In Pilot Socket on Outlet Side, Reducer Bushings, 1/4" Quick Connect Terminals (C, C, L, S), Slow Opening Feature, No Leads, No LP Kit |
| 752220 | 36C94-303 | Gas Valve, 1/2" x 3/4", straight thru, 24 VAC, Pilot (No plug in), delay opening 5 sec. (.006" orifice), slow opening, 3/16 terminal adapter on terminal #4, balance of terminals (4) are 1/4" spade, pressure switch on cap, Nat gas, Regulator set at 3.5 +/- .3 in WC at 110 KBTU/hr, Leak limiting hose barb (fitting) on regulator tower, Instruction sheet, LP gas conversion kit |



36C Series

(cont'd on next page)

WHITE-RODGERS CONTROLS

www.white-roddgers.com

GAS VALVES (cont'd)

| ITEM # | MODEL | DESCRIPTION |
|--------|-----------|---|
| 752326 | 36G22-254 | Universal Gas Valve, 24 VAC, 50/60 Hz, ½ x ½ NPT, straight thru, fast opening, inlet/outlet pressure taps, Regulator setting: 3.5 in WC at 110,000 BTU/Hr, inlet/outlet filters, (2) 1/4 in male spade terminals, pressure tap towers, mounting holes for 8-32 thread forming screws. Price reflects 1 valve. |
| 752241 | 36H32-304 | Gas Valve, 1/2" x 3/4", 24 VAC, Proven Pilot Valve, Fast Open, Electric On/Off Switch, 1/4" O.D Pilot Fitting included, LP Conversion Kit, 1/2" x 3/4" and 1/2" x 3/8 Bushings, Fast Open, flow – straight thru, replaces 36E36-304 |
| 752242 | 36H32-423 | Universal, 3/4" x 3/4", Reducer Bushings (Two 3/4" to 1/2"), 24V, 1/4" Male Spade Quick Connect Terminals, Nat. Gas (includes LP Conversion Kit), for use on non-piloted or intermittent pilot applications (not standing pilot). Replaces 36C68-423. |
| 752243 | 36H33-412 | Gas Valve, 3/4" x 3/4", 24 VAC, Proven Pilot Valve, Electric On/Off Switch, 1/4" O.D Pilot Fitting included, LP Conversion Kit, Two 1/2" x 3/4" Bushings. Single stage valve, Slow Open, flow – straight thru. |
| 752244 | 36H64-463 | 36H Two-Stage Gas Valve, 3/4" x 3/4", Reducer Bushings (Two 3/4" to 1/2"), 24V, 1.4" Male Spade Quick Connect Terminals, Nat. Gas (includes LP Conversion Kit), for use on non-piloted or intermittent pilot applications (not standing pilot). Replaces 36C76-406, 36C76-420, 36C76-462, and 36C76-463 and other models. |
| 752246 | 36H65-401 | Gas Valve, 3/4" x 3/4", 24 VAC, Proven Pilot Valve, Slow Open, Two Stage, Electric On/Off Switch, 1/4" O.D Pilot Fitting, LP Conversion Kit, Two 1/2" x 3/4" Bushings, flow – straight thru |
| 752303 | 36J22-214 | Combination Gas Valve, Single Stage, Fast Opening, Inlet/ Outlet pressure taps, Plastic hose barb (for connection to 1/4" Hose/Flexible Tubing), LP gas conversion kit, Inlet/Outlet reducer bushings (1/2 NPT x 3/8 NPT), Regulator calibrated to 3.5 ± 0.3" W.C. @ 100KBTU/Hr (Nat Gas), 24 VAC, 60 Hz, 1/2 x 1/2 NPT, Replaces 36G22-214 |
| 752304 | 36J24-214 | Combination Gas Valve, Single Stage, Slow Opening, Inlet/ Outlet pressure taps, Plastic Hose Barb (for Connection to 1/4" Hose/Flexible Tubing), LP Gas Conversion Kit, Inlet/Outlet Reducer Bushings (1/2 NPT x 3/8 NPT), Regulator Calibrated to 3.5 ± 0.3" W.C. @ 100KBTU/Hr (Nat Gas), 24 VAC, 60 Hz, 1/2 x 1/2 NPT, Replaces 36G24-214 |
| 752305 | 36J54-214 | Combination Gas Valve, 2 Stage, Fast Opening, Inlet and outlet pressure taps, Plastic hose barb (For connection to 1/4" Hose/flexible tubing), LP gas conversion kit, Inlet/Outlet reducer bushings (1/2 NPT to 3/8 NPT), Hi-Fire regulator calibrated to 3.5 ± 0.3" W.C. @ 100,000 BTU/Hr (Nat Gas), Lo-Fire regulator calibrated to 1.5 ± 0.3" W.C., 24 VAC, 60 Hz, 1/2 x 1/2 NPT, Replaces 36G54-214 |
| 752308 | 36J55-214 | Combination Gas Valve, 2 Stage, Slow Opening, Inlet and outlet pressure taps, Control to be shipped with switch in "ON" position, Plastic hose barb (For connection to 1/4" Hose/flexible tubing), LP gas conversion kit, Inlet/Outlet reducer bushings (1/2 NPT to 3/8 NPT), Hi-Fire regulator calibrated to 3.5 ± .3 W.C. @ 100,000 BTU/Hr (Nat Gas), Lo-Fire regulator calibrated to 1.5 ± .3 W.C., 24 VAC, 60 Hz, 1/2 x 1/2 NPT, Replaces 36G55-214 |



36H32-423



36H64-463



36J22-214



36J54-214

WHITE-RODGERS CONTROLS

www.white-rodders.com

FAN RELAYS

| ITEM # | MODEL | DESCRIPTION |
|--------|---------|---|
| 751130 | 90-290Q | Type 84, 24VAC Coil, SPNO. Coil Data: 90 Ohms DC Resistance, 125mA (Nominal), 3VA (Nominal), 4VA (Inrush) |
| 751132 | 90-293Q | Type 84, 24VAC Coil, SPDT. Coil Data: 90 Ohms DC Resistance, 125mA (Nominal), 3VA (Nominal), 4VA (Inrush) |
| 751134 | 90-294Q | Type 84, 115/120VAC Coil, SPDT. Coil Data: 2,000 Ohms DC Resistance, 25mA (Nominal), 3VA (Nominal), 4VA (Inrush) |
| 751140 | 90-370 | Type 184, 24VAC Coil, 50/60 Hz, SPDT. Coil Data: 77 Ohms DC Resistance, 125mA (Nominal), 3VA (Nominal), 4VA (Inrush) |
| 751142 | 90-374 | Type 184, 208/240VAC Coil, 50/60Hz, SPDT. Coil Data: 6050 Ohms DC Resistance, 12.5mA (Nominal), 3VA (Nominal), 4VA (Inrush) |
| 751144 | 90-380 | Type 184, 24VAC Coil, 50/60Hz, SPNO/SPNC. Coil Data: 77 Ohms DC Resistance, mA (Nominal), 3VA (Nominal), 4VA (Inrush) |
| 751146 | 90-384 | Type 184, 208/240VAC Coil, 50/60 Hz, SPNO/SPNC. Coil Data: 6050 Ohms DC Resistance, 12.5mA (Nominal), 3VA (Nominal), 4VA (Inrush) |
| 751814 | 8A04-1 | Enclosed Relay, 24VAC Coil Voltage, SPDT |



90-290Q



90-293Q/90-294Q



90-370



90-380

TRANSFORMERS

| ITEM # | MODEL | DESCRIPTION |
|--------|-----------|---|
| 751818 | 8A05A-101 | Fan Center, SPDT, 120VAC, 60Hz, 0.28A coil current, 14A @ 120VAC / 8A 240VAC FL, for single or 2 speed motors. |
| 751108 | 90-113 | Fan Control Center, 120VAC Primary 24VAC Secondary, SPDT Relay |
| 751137 | 90-340 | 2 Pole, Type 91, 24VAC Coil, DPDT, 2 Sets of Power Rated Contacts. 17.5 Ohms DC Resistance, 334 mA, 9.5VA (Nominal), 22VA (Inrush) |
| 751139 | 90-341 | 2 Pole, Type 91, 115/120VAC Coil, DPDT, 2 Sets of Power Rated Contacts. 420 Ohms DC Resistance, 66 mA, 9.5VA (Nominal), 22VA (Inrush) |
| 751147 | 90-T40F1 | Transformer, 40VA, 60 Hz, 120V Pri., 24V Sec., Foot Mount |
| 751150 | 90-T40M3 | Transformer, 40VA, 60 Hz, 120/208/240V Pri., 24V Sec., Multi-Mount |
| 751152 | 90-T75C3 | Transformer, 75VA, 50/60 Hz 120/208/240V Pri, 24V Sec, Foot Mount |
| 752650 | S82A-310 | Hub mount, 120VAC to 25VAC, 60Hz, 20VA, 10" leads (line), screw / spade terminals (load). |
| 752656 | S84A-310 | Hub mount, 120VAC to 25VAC, 60Hz, 40VA, 10" leads (line), screw / spade terminals (load), with plate. |



8A05A-101



90-340



90-T40F1



90-T75C3



S84A-310

ELECTRIC HEAT PRODUCTS

| ITEM # | MODEL | DESCRIPTION |
|--------|---------|---|
| 752022 | 24A34-1 | Electric Heat Sequencer, 1 Switch. On Timings, 1-20 Sec. Off Timings, 40-110 Sec. |
| 752047 | 24A34-3 | Electric Heat Sequencer, 2 Switches. On Timings, 1-20 Sec. Off Timings, 40-110 Sec. |



24A34-1

(cont'd on next page)

WHITE-RODGERS CONTROLS

www.white-rodders.com

ELECTRIC HEAT PRODUCTS (cont'd)

| ITEM # | MODEL | DESCRIPTION |
|--------|----------|---|
| 752030 | 24A34-21 | Single timing, heat on in 1 to 20 seconds, heat off in 1 to 50 seconds, double quick connect terminals for combination loads, -40°F to +150°F (-40°C to +66°C) ambient. |
| 752032 | 24A34-22 | Single timing, heat on in 15 to 45 seconds, heat off in 1 to 30 seconds, double quick connect terminals for combination loads, -40°F to +150°F (-40°C to +66°C) ambient. |
| 752034 | 24A34-23 | Single timing, heat on in 25 to 55 seconds, heat off in 15 to 45 seconds, double quick connect terminals for combination loads, -40°F to +150°F (-40°C to +66°C) ambient. |
| 752036 | 24A34-24 | Single timing, heat on in 30 to 75 seconds, heat off in 1 to 40 seconds, double quick connect terminals for combination loads, -40°F to +150°F (-40°C to +66°C) ambient. |
| 752038 | 24A34-25 | Single timing, heat on in 40 to 90 seconds, heat off in 1 to 30 seconds, double quick connect terminals for combination loads, -40°F to +150°F (-40°C to +66°C) ambient. |
| 752040 | 24A34-26 | Double timing, double pole, heat on in 1 to 20 seconds / 30 to 90 seconds, heat off in 40 to 90 seconds / 1 to 30 seconds, double quick connect terminals for combination loads, -40°F to +150°F (-40°C to +66°C) ambient. |
| 752042 | 24A34-27 | Combination relay 2 on single plate, heat on in 1 to 160 seconds, heat off in 1 to 160 seconds, double quick connect terminals for combination loads, -40°F to +150°F (-40°C to +66°C) range. |
| 752044 | 24A34-28 | Combination relay 2PDT, heat on in 1 to 160 seconds, heat off in 1 to 160 seconds, double quick connect terminals for combination loads, -40°F to +150°F (-40°C to +66°C) range. |
| 752046 | 24A34-29 | Single timing, heat on in 15 to 35 seconds, heat off in 25 to 55 seconds, double quick connect terminals for combination loads, -40°F to +150°F (-40°C to +66°C) ambient. |
| 752048 | 24A34-36 | Double timing, double pole, heat on in 1 to 20 seconds / 30 to 45 seconds, heat off in 45 to 110 seconds / 1 to 30 seconds, double quick connect terminals for combination loads, -40°F to +150°F (-40°C to +66°C) ambient. |
| 752050 | 24A34-37 | Double timing, double pole, heat on in 1 to 110 seconds, heat off in 1 to 110 seconds, double quick connect terminals for combination loads, -40°C to +150°F (-40°C to +66°C) ambient. |

UV LIGHTS AND ACCESSORIES

| ITEM # | MODEL | DESCRIPTION |
|--------|-----------|---|
| 752692 | UV100 | Single UV Light suitable for Slab Coil applications 3 tons or less, and 1200 CFM or less or where space permits only a Single Lamp. |
| 752696 | UVP-06207 | UV-C Replacement Lamp for UV100 and UV200 for UV Series Germicidal Light. |



UV100

HUMIDISTAT

| ITEM # | MODEL | DESCRIPTION |
|--------|----------|-------------------------|
| 707926 | 2271-100 | Humidistat – Horizontal |



– E.&O.E. – All Prices F.O.B. Our Warehouse – Subject to Change Without Notice – All Taxes Extra – May not be Available at All Branches –

WHITE-RODGERS CONTROLS

www.white-rodders.com

AIR CLEANERS

ELECTROSTATIC


| ITEM # | MODEL | DESCRIPTION |
|--------|--------------|--|
| 752750 | ACE-16X25X5 | 16" x 25" complete with filter. 5" |
| 752754 | ACE-20X25X5 | 20" x 25" complete with filter. 5" |
| 752760 | ACM2000M-108 | 20" x 25" 4" Media Air Cleaner Cabinet with MERV 8 filter, 2000CFM |



ACM2000M-108

ELECTROSTATIC — A+2000

| ITEM # | MODEL | DESCRIPTION |
|--------|-------------|----------------|
| 684390 | A0401-16251 | 16" x 25" x 1" |
| 684396 | A0401-16201 | 16" x 20" x 1" |
| 684392 | A0401-20251 | 20" x 25" x 1" |
| 684394 | A0401-20201 | 20" x 20" x 1" |



A+2000

MEDIA

| ITEM # | MODEL | DESCRIPTION |
|--------|-------------|--|
| 752844 | FR1400-100 | Filter Replacement 1400 CFM (F825-0548). Must Order In Multiples of 3 for Shipping Purposes. Price Reflects 3 Filters. |
| 752828 | FR1400M-108 | 16" x 25" x 4" MERV 8 Filter Replacement for ACM1400M cabinet. Price Reflects 3 Filters. |
| 752830 | FR1400M-111 | 16" x 25" x 4" MERV 11 Filter Replacement for ACM1400M cabinet. Price Reflects 3 Filters. |
| 752832 | FR1400U-108 | 16" x 25" MERV 8 Universal Filter Replacement for ACM1400U, ACM1400-100, ACM1400-101 and Competitive Trion Air Bear, Honeywell (F35, F100, F150, F200), Space-Guard 2400, Lennox BMAC-14C, and Carrier MACPAK. Shipped in Quantities of 3. Price Reflects 3 Filters. |
| 752846 | FR2000-100 | Filter Replacement 2000 CFM (F825-0549) Must Order In Multiples of 3 for Shipping Purposes. Price Reflects 3 Filters. |
| 752838 | FR2000M-108 | 20" x 25" x 4" MERV 8 Filter Replacement for ACM2000M cabinet. Price Reflects 3 Filters. |
| 752840 | FR2000M-111 | 20" x 25" x 4" MERV 11 Filter Replacement for ACM2000M cabinet. Price Reflects 3 Filters. |
| 752836 | FR2000U-108 | 20" x 25" MERV 8 Universal Filter Replacement for ACM2000U, ACM2000-100, ACM2000-101 and Competitive Trion Air Bear, Honeywell (F35, F100, F150, F200), Space-Guard 2200, Lennox BMAC-20C, and Carrier MACPAK. Shipped in Quantities of 3. Price Reflects 3 Filters. |



FR Series

ELECTRONIC

| ITEM # | MODEL | DESCRIPTION |
|--------|-----------|--|
| 752494 | F825-0432 | Electronic Air Cleaner Prefilter for SST1400-100, Emerson 14, Grainger 14 |
| 752496 | F825-0467 | Charcoal Filter W/Clips for SST1400-100, SST1400-100, 14C275-010, Replaces F825-0475 |
| 752582 | F859-0381 | Electronic Air Cleaner Air Flow Switch and Harness for adding Air Flow Switch Option to SST or UST 120 VAC Models, Replaces F859-0224 and F859-0324, F859-0380 |

- E.&O.E. - All Prices F.O.B. Our Warehouse - Subject to Change Without Notice - All Taxes Extra - May not be Available at All Branches -

WHITE-RODGERS CONTROLS

www.white-roddgers.com

HUMIDIFIERS AND PARTS

| ITEM # | MODEL | DESCRIPTION |
|--------|------------------|--|
| 707904 | HDT2600 | Drum Type. Rotating pad type, up to 2600 sq. ft., tight construction, all necessary parts for normal installation. |
| 708374 | HSP2600 | Steam Powered, 240V, Humidifies 1850 sq. ft. minimum with Flushing Timer and Filter |
| 708364 | HFT2100K | COMFORT PLUS Bypass flow-thru, with installation kit, 2121 sq. ft. |
| 707906 | H-40 | Plate Type, non-powered, plates not included, water reservoir outside of plenum. |
| 708380 | WRA01-0814-148 | 24V Solenoid Valve (Universal Kit) for HFT2100, HFT2700, HFT2900FP |
| 708381 | PAD-A04-1725-051 | Evaporator Pad (Includes Wick) for HFT2700, HFT2900FP |
| 708382 | PAD-A04-1725-052 | Evaporator Pad (includes Wick) for the HFT2100 |
| 708384 | A00-1128-005 | Saddle Valve assembly for all humidifiers |
| 707908 | 404700-02 | Motor and bracket assembly for VA-2 |
| 707918 | 404606-01 | Float valve assembly for VA-2 and L-40 |
| 707912 | 404384-01 | Media wheel for VA-2 |



HDT2600



HSP2600



HFT2100



WRA01-0814-148