

## **BANVIL 2000 COMMERCIAL AND INDUSTRIAL CEILING FANS**

[www.banvil2000.com](http://www.banvil2000.com)

### **INDEX**

COMMERCIAL CEILING FANS	
MODELS FP36, FP36R, FP56, FP56R.....	12-4
INDUSTRIAL CEILING FANS	
MODELS 160F7, 160F7-BK, 160F7-BRN, 160F7-220V, 160C7, 136F-10, 136C-10.....	12-2
MODEL 60F-7 .....	12-3
MOTOR AND FAN CONTROLLER .....	12-4

*Expert Service. Quality Products. Since 1960.*

# BANVIL 2000 COMMERCIAL AND INDUSTRIAL CEILING FANS

www.banvil2000.com

## INDUSTRIAL CEILING FANS

**MODELS 160F7, 160F7-BK, 160F7-BRN, 160F7-220V, 160C7, 136F-10, 136C-10**

**Gold Line — Extra Heavy Duty**

**Features:**

- Downrod diameter 7/8".
- Corrosion-resistant epoxy prime and finish coat on all metal housing and blades. The aerodynamically curved-tip aluminum blade results in maximum air delivery.
- Customized downrod lengths over 36" available. Also 16' cord with plug part # Cord-Wh16.
- Pre-wired with 16" cord and built-in strain relief.
- Use solid state infinite speed motor controls or church quiet control for one fan only (WC103).
- 9.5 mfd non-polar, weatherproof encapsulated, extra heavy-duty capacitor. (136F-10 has 4.0 uf capacitor)
- Permanent lubricated sealed TPI ball bearings.
- All metal, no plastic.
- Totally enclosed impedance protected cast motor.
- High grade cool steel motor laminations for maximum energy efficiency and heat dissipation for longer life.



ITEM #	MODEL	DESCRIPTION	CFM	AREA SQ/FT
810665	160F7-10	56" Diameter Ceiling Fan 10" Downrod, Down Blowing	34,500	2,100
810667	160C7-10	56" Diameter Ceiling Fan 10" Downrod , Up or Down Blowing	34,500	2,100
810662	136F-10	36" Diameter Ceiling Fan 10" Downrod, Down Blowing	12,000	800

MODEL	160F7	160C7*	136F-10*
Safety Cable	38" – 39"	38" – 39"	38" – 39"
Cord/Lead Wire	16"	16"	16"
Diameter Sweep	56"	56"	36"
Velocity (ft/m)	650	650	650
Volts	120	120	120
Amps	0.70	0.70	0.36
Watts	75	75	35
RPM (max)	320	350	400
Wiring	plug-in	plug-in	plug-in
Weight	24 lbs	24 lbs	17 lbs

\*Straight Blade Model

# BANVIL 2000 COMMERCIAL AND INDUSTRIAL CEILING FANS

[www.banvil2000.com](http://www.banvil2000.com)

## INDUSTRIAL CEILING FANS (cont'd)

### MODEL 60F-7

#### Silver Line — Heavy Duty

##### Features:

- Downrod diameter 7/8".
- Corrosion-resistant epoxy prime and finish coat on all metal housing and blades. The aerodynamically curved-tip blade results in maximum air delivery.
- All metal, no plastic.
- Permanent lubricated sealed TPI ball bearings.
- Totally enclosed impedance protected motor.
- Non-polar, weatherproof encapsulated, extra heavy-duty capacitor.
- Use solid state infinite speed motor controls or church quiet control (WC103).
- Heavy cast yoke for easy infield downrod change.
- Customized downrod lengths over 36" available. Also 16' cord with plug part # Cord-Wh16.



ITEM #	MODEL	DESCRIPTION	CFM	AREA SQ/FT
810664	60F7-10	56" Diameter Ceiling Fan 10" Downrod, Down Blowing	27,500	1,800

MODEL	60F-7
Safety Cable	60"
Cord/Lead Wire	60"
Diameter Sweep	56"
Velocity (ft/m)	600
Volts	120
Amps	0.70
Watts	75
RPM (max)	320
Wiring	plug-in
Weight	13 lbs

# BANVIL 2000 COMMERCIAL AND INDUSTRIAL CEILING FANS

[www.banvil2000.com](http://www.banvil2000.com)

## COMMERCIAL CEILING FANS

### MODELS FP36, FP36R, FP56, FP56R

#### Bronze Line — Commercial Duty

##### Features:

- Downrod diameter 7/8".
- Corrosion-resistant epoxy prime and finish coat on all metal housing and blades. The aerodynamically curved-tip blade results in maximum air delivery.
- All metal, no plastic.
- Permanent lubricated sealed TPI ball bearings.
- Totally enclosed impedance protected motor. Non-polar, extra heavy duty capacitor.
- Use solid state infinite speed motor controls or church quiet control (WC103).
- Heavy cast yoke for easy infield downrod change.
- Customized downrod lengths over 36" available. Also 16' cord with plug part # Cord-Wh16.
- For church quiet control use WC103 Control for one fan only.



ITEM #	MODEL	DESCRIPTION	CFM	AREA SQ/FT
810650	FP36	36" Diameter Ceiling Fan 10" Downrod, Down Blowing	10,500	700
810651	FP36R	36" Diameter Ceiling Fan 10" Downrod, Up or Down Blowing	10,500	700
810653	FP56	56" Diameter Ceiling Fan 10" Downrod, Down Blowing	22,000	1,700
810654	FP56R	56" Diameter Ceiling Fan 10" Downrod, Up or Down Blowing	22,000	1,700

MODEL	FP36	FP36R	FP56	FP56-R
Safety Cable	60"	60"	60"	60"
Cord/Lead Wire	60"	60"	60"	60"
Diameter Sweep	36"	36"	56"	56"
Velocity (ft/m)	600	600	600	600
Volts	120	120	120	120
Amps	0.35	0.35	0.55	0.55
Watts	40	40	65	65
RPM (max)	360	360	280	280
Wiring	plug-in	3 + ground	plug-in	3 + ground
Weight	9 lbs	9 lbs	13 lbs	13 lbs

## MOTOR AND FAN CONTROLLERS

ITEM #	MODEL	DESCRIPTION
810682	105F	120V, 10A, Variable Speed Control, Up to 4 Fans
810670	108C	20 AMP, 15 Fans, Reversing Switch



105F

**\*NOTE:** Solid State controls may introduce 60 cycle hum noise in fan motors.