

**TAPES AND DUCT PROTECTION FILM**  
www.venturetape.com / www.covalenceadhesives.com /  
www.eminentsupply.com / www.ductmate.com

**INDEX**

DUCT PROTECTION WRAP  
    PROGUARD PLASTIC FILM DUCT COVER..... 14-8  
    VENTURE TAPE® 1512..... 14-8  
DUCT TAPE (HIGH TENSILE STRENGTH) PREMIUM CLOTH TYPE ..... 14-2  
FOIL TAPE (FSK (FOIL SCRIM KRAFT)) REINFORCED ALUMINUM  
    VENTURE TAPE® 1525CW..... 14-3  
FOIL TAPE (PLAIN ANNEALED DEAD SOFT ALUMINUM)  
    VENTURE TAPE 1520CW® ..... 14-2  
    VENTURE TAPE 3243..... 14-3  
HURRICANE TAPE™ ..... 14-5  
SHEATHING TAPE  
    VENTURE TAPE 1585CW®-P2..... 14-4  
TAPES — MISCELLANEOUS  
    ELECTRICAL TAPE..... 14-7  
    FOAM TAPE ..... 14-7  
    PACKAGING TAPE ..... 14-7  
    TEFLON TAPE..... 14-7  
UL181B-FX APPROVED TAPE  
    VENTURE TAPE® 1599B..... 14-4  
VENTURECLAD® JACKETING SYSTEMS  
    VENTURECLAD® 1577CW ..... 14-6  
    VENTURECLAD PLUS® 1579CW..... 14-6

*Expert Service. Quality Products. Since 1960.*

## TAPES AND DUCT PROTECTION FILM

### DUCT TAPE (HIGH TENSILE STRENGTH) PREMIUM CLOTH TYPE

#### APPLICATIONS

- Heating, air conditioning, ventilating, and refrigeration
- Asbestos removal applications
- Sealing of seams and joints in metal air handling systems
- Sand and media blasting applications
- Manufacture of flexible duct equipped with metal collars
- Bonding, protecting, holding, repairing, and patching



ITEM #	MODEL	DESCRIPTION	COLOR
706024	Generic	1" x 60 yards	Silver/Gray
706025	Generic	1-1/2" x 60 yards	Silver/Gray
706026	Generic	2" x 60 yards	Silver/Gray
706022	Generic	2" x 60 yards	Yellow

### FOIL TAPE (PLAIN ANNEALED DEAD SOFT ALUMINUM)

#### VENTURE TAPE 1520CW®

Venture Tape 1520CW® COLD WEATHER FOIL is an annealed aluminum foil coated with Venture's CW® cold weather solvent acrylic pressure sensitive adhesive. The malleable foil applies easily to both fibrous and sheet metal ducts and conforms to irregular surfaces. Venture Tape 1520CW® excels in demanding temperature and humidity applications and provides superior performance and durability over a wide range of environmental conditions.



#### Features and Benefits of 1520CW®:

- UL723 Listed (5/10 Flame/Smoke rating)
- U.S. Coast Guard Approved (CGA# 164.112/63/0)
- Conforms to British standards BS 476
- Specifically designed for cold weather conditions; also excels in high heat and humidity
- High performance insulation tape is ideal for use as a vapor seal for reinforced fiberglass or mineral wool thermal insulation
- May also be used on FSK systems
- Venture CW® cold weather solvent acrylic adhesive performs well over a wide temperature range
- Hand tearable allows for easy installation
- In stock product available for immediate delivery

ITEM #	MODEL	DESCRIPTION	COLOR
706068	Generic	2" x 50 yards	Aluminum
706071	Generic	3" x 50 yards	Aluminum
706076	1520CW-Venture	2" x 50 yards	Aluminum
706077	1520CW-Venture	3" x 50 yards	Aluminum

## TAPES AND DUCT PROTECTION FILM

### FOIL TAPE (PLAIN ANNEALED DEAD SOFT ALUMINUM) (cont'd)

#### VENTURE TAPE 3243

Venture Tape 3243 is a 2.0-mil (50µm) annealed aluminum foil coated with a high temperature, extremely aggressive solvent acrylic pressure sensitive adhesive. Specifically designed for high heat flue closure applications, Venture 3243 applies easily to sheet metal ducts on flat and irregular surfaces. Venture Tape 3243 excels in demanding temperature applications and provides superior performance and durability over a wide range of environmental conditions.



#### Features and Benefits of 3243:

- High temperature, high performance duct closure tape is specifically designed for use as a flue pipe closure tape
- May be used as a heat shield for welding
- High performance solvent acrylic adhesive performs well over a wide temperature range
- Hand tearable allows for easy installation
- Excels in a wide range of environmental conditions
- In stock product available for immediate delivery

ITEM #	MODEL	DESCRIPTION	COLOR
706046	3243-Venture	3" x 50 yards Hi-Temp	Aluminum

### FOIL TAPE (FSK (FOIL SCRIM KRAFT)) REINFORCED ALUMINUM

#### VENTURE TAPE® 1525CW

Venture Tape® 1525CW COLD WEATHER FSK is a 5.0-mil (125µm) foil/scrim/kraft (FSK) lamination coated with a cold weather solvent acrylic pressure sensitive adhesive. Versatile FSK applies easily to both fibrous and sheet metal ducts and easily conforms to irregular surfaces. Venture Tape® 1525CW excels in demanding temperature and humidity applications and provides superior performance and durability over a wide range of environmental conditions.



#### Features and Benefits:

- UL723 Listed
- Specifically designed for cold weather conditions
- Tri-directionally reinforced 2 x 3 squares per inch fiberglass scrim, UL Listed FSK lamination
- Also excels in high heat and humidity conditions
- High performance insulation tape is ideal for use as a vapor seal for reinforced fiberglass or mineral wool thermal insulation
- Venture Tape® CW cold weather solvent acrylic adhesive performs well over a wide temperature range
- Facing meets ASTM C1136, Type II, IV
- In stock product available for immediate delivery

ITEM #	MODEL	DESCRIPTION	COLOR
706069	Generic	2" x 50 yards	Alum-FSK
706070	Generic	3" x 50 yards	Alum-FSK
706078	1525CW-Venture	2" x 50 yards	Alum-FSK
706079	1525CW-Venture	3" x 50 yards	Alum-FSK

## TAPES AND DUCT PROTECTION FILM

### UL181B-FX APPROVED TAPE

#### VENTURE TAPE® 1599B

Venture Tape 1599B is a 3-mil (76µm) UV resistant bi-axially oriented polypropylene (BOPP) tape coated with a Venture's CW® cold weather solvent acrylic adhesive. Hand tearable, thinner and tougher than traditional duct tapes, Venture 1599B lasts longer and will not delaminate with age. Available in Silver, Black, and Clear, Venture Tape 1599B provides easy application and superior performance and durability over a wide range of temperatures and environments, including high heat desert conditions.



#### Features and Benefits:

- **Specifically designed to meet UL181B-FX and AS4254 requirements**
- High performance flexible duct closure tape performs well over a wide temperature range
- Venture CW® all weather acrylic adhesive applies easily at temperatures as cold as -35°F (-37°C)
- Ideal for use on metal and metal connections
- Higher adhesion and tack than traditional cloth duct tapes
- Excels in high heat and humidity conditions
- In stock product available for immediate delivery

ITEM #	MODEL	DESCRIPTION	COLOR
706073	UL-181B-FX	2" × 60 yards	Black
706074	1599B	2" × 120 yards	Black

### SHEATHING TAPE

#### VENTURE TAPE 1585CW®-P2

Venture Tape 1585CW-P2 is a printed polypropylene sheathing tape coated with an aggressive acrylic pressure sensitive adhesive (PSA) designed for use as a closure system and vapor seal on all interior and exterior sheathing materials. Venture Tape 1585CW-P2 exceeds most building code requirements and can be used for new construction as well as repair on all vapor barrier materials. CCMC approved, Venture Tape 1585CW-P2 is the highest performing, highest value product on the market today.



#### Features and Benefits:

- High performance sheathing tape installs and performs well over a wide temperature range
- Excellent vapor barrier tape on polyethylene film
- Performs well as a seam tape on extruded foam products such as **Styrofoam®** and **Foamular®**
- Applies to all major housewraps including **Tyvek®** and **Typar®**
- Great for use as a sealing tape on **DensGlass Gold®** and other sheathing brands

ITEM #	MODEL	DESCRIPTION	COLOR
706080	1585CWP2	2-1/2" × 72 yards	Red

## TAPES AND DUCT PROTECTION FILM

### HURRICANE TAPE™ (POLYETHYLENE ACRYLIC ADHESIVE WITH WOVEN FIBERS)

Hurricane Tape™ is a polyethylene acrylic adhesive tape that's composed of woven polyethylene plastic known as warp and weft tapes. These tapes are arranged in a weave pattern of right angles to promote the tear strength of the tape. A plastic substrate is laminated to the scrim for increased integrity of the tape.

The adhesive of choice is a water-based acrylic, designed to adhere in any condition particularly in cold and wet temperatures. The common use for HURRICANE TAPE™ is to minimize shattering of windows particularly in severe wind storms such as hurricanes or tornadoes. The tough weave design combined with the aggressive adhesive is extremely effective in keeping pieces of glass intact, minimizing shatter.

In addition to glass applications, an array of uses are appropriate for HURRICANE TAPE™ e.g. temporary repairs on your car, boat or RV. HURRICANE TAPE™ is a very effective packaging or strapping tape as well.



#### Features and Benefits:

- Extremely strong and tear resistant enabling up to 10x less tape used in comparison to other tapes where strength is called for in an application.
- Aggressive acrylic adhesive sticks well to many surfaces but will remove with minimal amount of residue. Versatile for many temporary and permanent applications.
- Conformable and can be applied to irregular surfaces.
- Five colours and available custom ordered colours for colour coding or surface matching.
- Will not rot like organic tapes like duct tape and will not develop health hazard mold from prolonged exposure to moisture.

ITEM #	MODEL	DESCRIPTION	COLOR
706020	Hurricane	2" x 60 yards	White

## TAPES AND DUCT PROTECTION FILM

### VENTURECLAD® JACKETING SYSTEMS

#### VENTURECLAD® 1577CW

VentureClad® 1577CW is a zero permeability, absolute vapor barrier for insulation cladding and jacketing applications. A 5-ply, self adhesive material installs quickly and easily with no special tools required, resulting in significant time, labour, and cost savings. VentureClad® 1577CW exceeds most building code requirements and can be used for new construction as well as repair on existing structures. Available in natural aluminum, white, black, and stucco embossed texture, VentureClad® 1577CW is the highest performing, highest value product on the market today.



#### Features and Benefits of 1577CW:

- High performance jacketing product performs well over a wide temperature range; -30°F to 300°F (-34°C to 149°C) service temperature
- VentureTape® CW cold weather acrylic adhesive applies easily at temperatures as cold as -10°F (-23°C)
- Zero permeability, absolute vapor barrier
- High puncture and tear resistance
- Contains tested and approved mold inhibiting agents
- Self adhesive material installs easily with no off-site fabrication required
- Exceeds standard building design requirements (UL 723 10/20 Flame Spread/Smoke Rating)

#### VENTURECLAD PLUS® 1579CW

VentureClad Plus® 1579CW is a patented\*, zero permeability, absolute weather and vapor barrier for insulation cladding and jacketing applications. A 13-ply, self adhesive material is as tough as metal jacketing materials but can be installed quickly and easily with no special tools required. VentureClad Plus® 1579CW exceeds most building code requirements and can be used for new construction as well as repair on existing structures. Available in natural aluminum, white, and stucco embossed texture, both with and without adhesive, VentureClad Plus® jacketing is the highest performing, highest value product on the market today.

#### Features and Benefits of 1579CW:

- Flexible, strong, fabric reinforced insulation cladding product combines vapor barrier function with heavy-duty all weather mechanical protection
- Ultra high performance jacketing product performs well over a wide temperature range; -30°F to 300°F (-34°C to 149°C) service temperature
- VentureTape® CW cold weather acrylic adhesive applies easily at temperatures as cold as -10°F (-23°C)
- Zero permeability, absolute vapor barrier
- High puncture and tear resistance
- Contains tested and approved mold inhibiting agents
- Self adhesive material installs easily with no off-site fabrication required
- Ideal for use over all types of insulation materials including fiberglass, mineral wool, calcium silicate, perlite, urethane and polystyrene
- Exceeds standard building design requirements (UL 723 50/75 Flame Spread/Smoke Rating)



#### VentureClad® 1577CW and VentureClad Plus® 1579CW

ITEM #	MODEL	DESCRIPTION	COLOR
706048	1577CW	23" x 50 yards	Natural Aluminum
C705199	1577CWE	23" x 50 yards	Stucco Embossed
C705199	1579CW*	23" x 25 yards	Natural Aluminum
706054	1579CWE*	23" x 25 yards	Stucco Embossed



1577CW

\*Seam sealing tape must be ordered with each roll of 1579CW/CWE and installed as a system, see below.

#### Sealing Tape for 1579CW/CWE Systems

ITEM #	MODEL	DESCRIPTION	COLOR
C705199	1577CW-E-FA602	4" x 50 yards	Embossed Aluminum
C705199	1577CW-FA599	4" x 50 yards	Natural Embossed



1579CW

– E.&O.E. – All Prices F.O.B. Our Warehouse – Subject to Change Without Notice – All Taxes Extra – May not be Available at All Branches –

## TAPES AND DUCT PROTECTION FILM

### TAPES — MISCELLANEOUS

#### FOAM TAPE

ITEM #	MODEL	DESCRIPTION	COLOR
706905	MA-FT1	2" x 30 feet	White
706016	1007	2" x 30 feet x 1/8" thick	White

#### TEFLON TAPE

ITEM #	MODEL	DESCRIPTION	COLOR
707622	—	1/2" Teflon	White
707624	—	1/2" Teflon-ULC	Yellow
706018	61-70820	Teflon	Yellow

#### ELECTRICAL TAPE

ITEM #	MODEL	DESCRIPTION	COLOR
706012	MA-C6408	Electrical Tape	Black
706040	13229	3/4" x 60 feet	Black
706042	—	3/4" x 66 feet	Black
706044	—	3/4" x 66 feet	Yellow

#### PACKAGING TAPE

ITEM #	MODEL	DESCRIPTION	COLOR
706028	—	2" x 330 feet	Clear

## TAPES AND DUCT PROTECTION FILM

### DUCT PROTECTION FILM (DUCT WRAP)

#### VENTURE TAPE® 1512

VentureTape® 1512 is a self-wound clear tape made from a co-extruded multi-polymer backing coated with a high-tack adhesive system to help provide surface protection for a variety of surfaces. This product is primarily used as a duct protection film.



ITEM #	MODEL	DESCRIPTION	COLOR
706075	1512-FA709	24" x 200 feet	Clear
C705199	1512-FA710	36" x 200 feet	Clear

### PROGUARD PLASTIC FILM DUCT COVER

ProGuard is designed to be placed over the opening of the ductwork during storage and transportation to protect the inside of ductwork from dust, dirt and other particles that can lead to poor indoor air quality.

#### Heavy Duty Grade

ProGuard Heavy Duty is a dual-ply polyethylene film with a high-tack adhesive coating. It is specially formulated to keep film attached and leave no residue when removed. Its unique manufacturing process gives ProGuard Heavy Duty unmatched puncture resistance, strength, elongation, and workability.



ITEM #	MODEL	DESCRIPTION	COLOR
715942	PG24	24" x 200 feet	Clear
715944	PG36	36" x 200 feet	Clear
715946	PG48	48" x 200 feet	Clear

#### Standard Grade

ProGuard Standard Grade is an economical single-ply film with a low-tack adhesive coating.

ITEM #	MODEL	DESCRIPTION	COLOR
715948	PG24C	24" x 200 feet	Clear
715950	PG36C	36" x 200 feet	Clear
C705199	PG48C	48" x 200 feet	Clear